

Technical Data Sheet

CODE 65158

AIR DOOR H AD1500 T

Air curtains




Certifications



TECHNICAL AND PERFORMANCE DATA

Absorbed Current max (A)	18	Delivery 1st speed (l/s)	528
Frequency (Hz)	50	Delivery 1st speed (m³/h)	1900
Max ambient temperature for continuous operation (°C)	25	Max delivery at max speed (l/s)	611
Max. absorbed power at max speed (W)	10650	Max delivery at max speed (m³/h)	2200
Number of speeds	2	Power setting 1 (W)	3300
Voltage (V)	400	Power setting 2 (W)	6700
Weight (Kg)	18	Power setting 3 (W)	10000
Airflow speed at max speed (m/s)	9.5	Sound pressure level Lp [dB (A)] 2m - max speed	59
Airflow speed at min speed (m/s)	8.5	Sound pressure level Lp [dB (A)] 2m - min speed	57

DIMENSIONS



Size A (mm)	1500
Size B (mm)	260
Size C (mm)	190

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 65158

AIR DOOR H AD1500 T

Air curtains



DESCRIPTION

- Aluminium front panel with satin finish, colour silver, and air inlet grille comprising 9 horizontal sections of polished aluminium. Rear pressed steel casing, colour black, functions as a frame to which all internal components are fixed. End caps moulded in ABS thermoplastic resin, colour black.
- Nominal width of appliance: 1500 mm.
- Twin-shaft induction motor with thermal overload protection, 2 speeds.
- Minimum air flow: 1900 m³/h
- Maximum air flow: 2200 m³/h
- 2 tangential fans moulded in thermoplastic resin (SAN) and ultrasonically welded, colour black, force air through a longitudinal vent located in the underside of the appliance.
- Electric battery with thermistors (PTC) featuring high thermal yields and reduced aerodynamic drag, protected against overtemperatures and power surges.
- Fan shutdown system by 30" after switching off the heating element.
- Infrared remote control for switching on/off, selecting the desired operating speed and switching on the heating element. These same controls are also available on the front panel of the appliance (3 buttons).
- Adjustable flaps for orientation of air stream.

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com